

Better Brooding of exotic birds

Altricial species of birds (including all parrots and birds of prey) are blind and helpless when they hatch and it is some weeks before they are able to move around, control their body temperature and feed themselves.

During this period the young birds need to be kept in a clean, temperature controlled environment as free as possible from airborne contaminants such as fungal spores and dust. As they grow and develop down and feathers they can gradually tolerate lower temperatures and the breeder needs to be able to reduce the chamber temperature easily, whilst still maintaining control. Young birds also benefit from being able to see humans from within the chamber; during this early stage in their development it is essential for young birds to become familiar with the presence of people if they are to be tame in adulthood.

Primary function

The new Octagon TLC-40 and TLC-50 brooders fulfil all these functions very cost effectively and can also double as a Hospital Cage for sick or injured birds. The two models differ in size; the TLC-40 has an effective volume of 40 litres (10 US gallons) and the TLC-50, 100 litres (26 US gallons). Furthermore each model is available with either Eco or Advance control system. The Eco provides digital control and read-out of temperature whereas the Advance also shows humidity, includes temperature and power failure alarms and can be further supplemented by Brinsea's optional EX Humidity Pump to provide full control of humidity too. The Advance versions include switchable internal LED lighting which is both efficient and effective.

Hygiene

With hygiene a top priority for your birds, the TLC-40 and 50 have been carefully designed to make cleaning as easy as possible. The lower half of the cabinets and doors are removable allowing them to be scrubbed and immersed. It is also easy to wipe clean the high gloss finish of the ABS plastic upper cabinet and the fan guard is simply detached to allow access to clean the fan. Even the heater is encased in a metal tube making cleaning easy. The control circuit is housed away from the chamber for reliability.

Airflow in the TLC-40 and TLC-50 has been carefully optimized to ensure consistent distribution of heat, so that all chicks are at the same temperature but with the fan maintaining gentle airspeeds so that down and dust are not blown around.

The design of the air circulation system results in a slight positive pressure within the chamber which resists the inflow of any unfiltered air from outside. This use of slight pressure differences is a proven method in hospital isolation wards to resist the spread of airborne bio-hazards. This positive pressure results in a small but essential airflow through the brooder chamber with fresh air drawn in through the inlet 2-stage electrostatic filter and into the chamber and stale air is discharged around the door and through the adjustable vent. As internal air is circulated it passes through two internal 2-stage electrostatic filters which remove airborne dust, spores and bacteria. All the filters are washable and replacement filter sets are available from Brinsea or from your local stockist.

To order quote part number HD021.



*Easy clean
cabinet design*

Brinsea
Incubation Specialists


BROODERS

TLC-40 and 50

- Accurate and adjustable digital temperature control
- Smooth, easy-to-clean interior
- No vulnerable edges for birds to chew
- Positive pressure with gentle fan ventilation
- Twin stage filter, for removal of harmful bacteria and fungi
- Water reservoir for increasing humidity with external top up
- Permanent calibrated digital temperature control with additional features and flexibility in Advance versions
- Tough, clear hinged door with secure catch
- Choice of two generous sizes suitable for a wide range of species
- 2 year guarantee (subject to simple online registration)



Water reservoir with evaporating block



Tough hinges



Filter set



optional EX humidity pump

Humidity

Warm air at brooding temperature can result in dehydration of the hatchlings so the TLC-40 and 50 incorporate a water reservoir over which air is circulated to increase humidity within the chamber. The water reservoir is filled from outside the unit and is clear, allowing the user to monitor the water level. The reservoir contains white evaporating block to help increase humidity and these blocks are available from Brinsea Products or your local stockist. The water reservoir is removable for cleaning.

The low weight of the TLC-40 and 50 make them easy to carry.

Guarantee

The TLC-40 and 50 are fully guaranteed and will be repaired or replaced if a fault should arise within the guarantee period (see terms of guarantee). Brinsea Products Ltd and their agents will not be responsible for loss or damages in the event of a failure, however caused, and the user is advised to arrange their own insurance cover where loss of power, mechanical or electrical failure might result in unacceptable losses.

In order that we can continue our policy of innovation and improvement we reserve the right to alter specifications without notice.

Brinsea Products Ltd.

Station Road, Sandford, N. Somerset BS25 5RA UK
Tel: +44 (0) 845 226 0120 Fax: +44 (0) 1934 820250

www.brinsea.co.uk

Brinsea Products Inc.

704 N. Dixie Avenue, Titusville, FL32796, USA
Tel: 1-888-667-7009 Fax: (321) 267 6090

www.brinsea.com

SPECIFICATIONS	TLC-40 Eco	TLC-40 Advance	TLC-50 Eco	TLC-50 Advance
Digital temperature control	•	•	•	•
Display choice of °C or °F	•	•	•	•
Digital Humidity display		•		•
Water pan for humidity	•	•	•	•
EX humidity pump option		•		•
Temperature alarm		•		•
Overall height (mm)	470	470	550	550
Overall height (inches)	18½	18½	21½	21½
Overall width (mm)	485	485	690	690
Overall width (inches)	19	19	27	27
Overall depth (mm)	385	385	490	490
Overall depth (inches)	15	15	19½	19½
Floor area (mm)	400 x 300	400 x 300	600 x 400	600 x 400
Floor area (inches)	15½ x 12	15½ x 12	23½ x 15½	23½ x 15½
Effective volume (litres)	40	40	100	100
Effective volume (US gallons)	10	10	26	26
Power consumption (Watts) Max	150	150	150	150
Typical	85	85	100	100
Power supply	115v, 60Hz or 230v 50Hz as ordered			
Weight (Kg)	6.7	6.7	8.7	8.7
Weight (lbs)	15	15	19	19